

## Mifare Two Doors Access Controller



### 名稱

Mifare Two Doors Access Controller

### 型號

**PC-3764**

### 品牌

Pegasus

### Agent

**PROFIT (OA) LTD** [www.profitoa.com.hk](http://www.profitoa.com.hk)

### 產品特色

- Can connect four external readers (PUA-310/M etc.) for four-door access control.
- Free Access function
- With tamper switch and two loop sensor input to trigger alarm when case is tampered or loop is intruded.
- Could retain events, personal maps and real time clock for 10 years as power failed.
- With built-in RS -232C / RS-422 / RS-485 and optional TCP/IP interface to configure PC controlled networking systems through Pegasus [PCP-832-XX multi-channel controller](#).
- With built-in quartz real time clock for time zone control & time recording.
- Cards add/delete/inquire can be executed for each door individually in single/ block of range or by read & learning by manual operation.
- 9,999 card holders / 6000 events for access and/or time attendance application

### 產品規格

Model No.	<b>PC-3764</b>
Mounting:	Surface mount
On-line interface:	RS -232C , RS-422 or RS-485, TCP/IP
Transmission rate:	300-19,200 bps, N,8,1 (default 4,800 bps)
Display:	With 16 x 2 lines LCD to display weekday, time, ID number, date, buffer counter...etc
Keypad:	4 x 3 metallic or membrane keypad for system programming
Indicators:	LED's ( one bicolor and one yellow ) and buzzer for sound indication
Inputs:	Exit, Door sensor, two Weigand port
Outputs:	Door, alarm relay drivers, one wire serial output (open collector / RS -232C selectable) printer, multiple relays driving
Power input / current:	12V DC / 130mA with LED back lighted
Operation temperature:	-1 0°C ~ 55°C
Humidity:	20%~90% RH, Non condensation
Dimensions:	174(L)x 100(W)x 45(H)mm
Weight:	740g

\*所載規格，本公司有修改權利，如與實品不符，以實品為準

